

























NEW STYLE ALLUMIA KNX CONTROL DEVICES

PA refers to the front plate type only.

System 44 is a modular system providing multiple options of control, style and finish. You will need to specify the mounting frame, touch control and front plate + any other features that are required when ordering.

ALLUMIA (Aluminium) Touch is born from a sophisticated union between technology and design.

During the night you can always identify the light command thanks to its delicate LED light. these plates are elegant pieces of contemporary furniture.

AVE offers a range of automation products aimed at the hotel and residential home using proprietary protocols (described in the technical catalogue) plus KNX protocol

Electronic multi-touch control - mono stable output-relay multiple points NO-contact 2A 230V~ Dry contact - controlled by touching the frontal area of the finishing plate or from multiple points with NO push buttons - mono stable, bi stable or timed operating modalities, curtains with interlock with low consumption for identification in the darkness

Home and hotel automation devices with multi-touch configurable commands to control lighting, shutter and recall scenarios. Visual and acoustic feedback command and viewing the status of the actuator: Light on / off, Shutter Open/ Close/ Move, etc. It is possible to select the sensitivity of a device at the touch of the plate or, 4mm distance from it. Powered by Home automation power supply.



444KNXT2B

444KNXT2B

Toggle control device KNX compatible with 2 channels - toggle white colour - supplied with no. 1 plastic white ring - 1 module



444KNXT2CR

Toggle control device KNX compatible with 2 channels - toggle white chrome - supplied with no. 1 plastic chrome ring - 1 module

444KNXT2CR



444KNXT20T

Toggle control device KNX compatible with 2 channels - brass toggle - supplied with no. 1 brass ring - 1 module

444KNXT2OT

Functions

Commands	Switch	Dimmer	Scene	Shutter and Blinds	Send Value	Control Value	Multi-action (3+3 Long P.)
	On/Off	Increase/Decrease	1 - 64	Up + Stop	Send Value n.1	Unforced + Off	On/Off
	On	Increase	Save Scene	Down + Stop	Send Value n.2	Unforced + On	Up/Down
	Off	Decrease		Up/Down + Stop	Send Value n.3	Forced + Off	Scene
				Up	Send Value n.4	Forced + On	Send Value (0-255)
				Down	Send Value n.1 (long. P.)		Send Value (0-100%)
				Up/Down	Send Value n.2 (long. P.)		HVAC
				Stop	Send Value n.3 (long. P.)		
				Open/Closed Slats	Send Value n.4 (long. P.)		
				Open Slats			
				Closed Slats			



■ 44PANT21ALS 86 9 Alluminio naturale spazzolato Natural brushedaluminium Mounting support to be used with 2x 442TC13Rblank insert O 96 **■ 44PANT21ANS** 44A02 Alluminio antracite spazzolato Anthracite brushedaluminium 44PANT21ALS **■ 44PANT22ALS** 86 9 Alluminio naturale spazzolato Natural brushedaluminium Mounting support required to fit UK 96 00 **■ 44PANT22ANS** back box Alluminio antracite spazzolato 44A02 Anthracite brushed aluminium 44PANT22ANS ■ 44PAN01ALS 118 9 Alluminio naturale spazzolato Mounting support to be used with 4x 442TC13Rblank insert Natural brushedaluminium 96 **■ 44PAN01ANS** 44A03 Alluminio antracite spazzolato Anthracite brushedaluminium 44PAN01ALS ■ 44PAN02ALS 118 9 Alluminio naturale spazzolato Natural brushedaluminium Mounting support to be used with 2x ē 442TC13Rblank insert ■ 44PAN02ANS 96 44A03 Alluminio antracite spazzolato Anthracite brushedaluminium 44PAN02ANS 44PAN03ALS 118 9 Alluminio naturale spazzolato Mounting support required Natural brushedaluminium 000 to fit UKbackbox 96 000 **■ 44PAN03ANS** 44A03 Alluminio antracite spazzolato Anthracite brushedaluminium 44PAN03ALS **44PAN04ALS** 141 9 Alluminio naturale spazzolato

96

44PAN04ANS

Mounting support required to fit UKbackbox

44A04

Natural brushedaluminium

Alluminio antracite spazzolato

Anthracite brushedaluminium

■ 44PAN04ANS