



Paweł Tatara

fol. Krzysztof Zgola

stinger

stinger

The high-quality hybrid spotlight used in the Stinger family is made of optical polycarbonate for even distribution of light. A black collar around the lens reduces the glare effect even further. The movable head rotates around its axis (350°) as well as up and down (170°), allowing spot lighting to illuminate any point. The Stinger range offers two versions, a 12W variant and a more powerful, i.e. 25W, one as well as spotlights with a rail adapter. The STINGER range is distinguished by the availability of optional accessories to help achieve the desired lighting effect. There is a honeycomb screen and a glare reduction ring as well as interchangeable optics to further enhance the control of the light beam. What is more, the Stinger range offers a selection of three colour temperatures and a DALI2 function to control the amount of light.



stinger 80 NT / ad 3F / pure ad 3F





stinger 80 ad 3F + antiglare ring




stinger pure 80 ad 3F

Model		On-Off	Switch DIM	DALI2	PhaseOut	Accessories	Black	White	Mixed	CR198-2700K	CR198-3000K	CR198-4000K	Spot 12°	Medium 42°	Wide 53°
							.02	.03	.99	.927	.930	.940	.S	.M	.W
Stinger Pure ⊕															
1	80 AD 3F	1x 15W1000lm	7.1883	7.2914	7.1884		•	•	•	•	•	•	•	•	•
2	80 AD 3F	1x27W1800lm	7.1885	7.2915	7.1886		•	•	•	•	•	•	•	•	•
Stinger ⊕															
1	80 NT	1x 15W1000lm	2.1770	2.2916	2.1771	2.1772	•	•	•	•	•	•	•	•	•
2	80 NT	1x27W1800lm	2.1776	2.2917	2.1777	2.1778	•	•	•	•	•	•	•	•	•
3	80 AD 3F	1x 15W1000lm	7.1773	7.2918	7.1774	7.1775	•	•	•	•	•	•	•	•	•
4	80 AD 3F	1x27W1800lm	7.1779	7.2919	7.1780	7.1781	•	•	•	•	•	•	•	•	•
Stinger Accessories															
1	Honeycomb louvre ^o	[option]				9.1800.02									
2	Antiglare ring	[option]				9.1801	•	•	•						
	Optic SPOT ^o	[option]				9.1802.02									
	Optic MEDIUM ^o	[option]				9.1803.02									
	Optic WIDE ^o	[option]				9.1804.02									





Stinger

1 2





90°
350°

1





170°
350°

2





170°
350°

3



170°
350°

4



170°
350°

Stinger — accessories

1



2



details subject to change.

