


STRAL

KHORI D40

KHORI D40 Bollard available in 4 heights: 30 cm, 50 cm, 70 cm, and 90 cm in AISI 316L stainless steel.

Bollard body available in 4 cm and 7 cm diameter versions for different de-sign requirements. Colour tempera-ture from 2700K, 3000K and 4000K.

Polycarbonate diffuser with inte-grated roto-symmetrical diffusing optic. Integrated driver. Fixing by anchor bolt with integrated cable routing or on flange for floor instal-lation. HCT surface finish available in three colour variants.



Output flux	335 lm
Luminous flux (Tj=25°C)	988 lm
Luminaire power	7 W
Light source type	LED
Color temperature	2700K
Optics type	PC Lens
Optics	Rotosymmetrical
CRI	CRI>=80 (typical - tolerances according to EN62717)
Life time	L80/B10 @100.000h Ta=25°C

Output flux	335 lm
Luminous flux (Tj=25°C)	988 lm
Luminaire power	7 W
Light source type	LED
Color temperature	2700K
Optics type	PC Lens
Optics	Rotosymmetrical
CRI	CRI>=80 (typical - tolerances according to EN62717)
Life time	L80/B10 @100.000h Ta=25°C

Output flux	335 lm
Luminous flux (Tj=25°C)	988 lm
Luminaire power	7 W
Light source type	LED
Color temperature	2700K
Optics type	PC Lens
Optics	Rotosymmetrical
CRI	CRI>=80 (typical - tolerances according to EN62717)
Life time	L80/B10 @100.000h Ta=25°C

Output flux	335 lm
Luminous flux (Tj=25°C)	988 lm
Luminaire power	7 W
Light source type	LED
Color temperature	2700K
Optics type	PC Lens
Optics	Rotosymmetrical
CRI	CRI>=80 (typical - tolerances according to EN62717)
Life time	L80/B10 @100.000h Ta=25°C



F W Lighting - The Light House - 37 Wadham Grove - Emersons Green - Bristol - BS16 7DX

+44 (0) 7891 919 169

info@fw-lighting.com

www.fw-lighting.com