


# STRAL


## LOCH M90

LOCH M90 The spacer integrated with the lamp body makes the product compact. Made of AISI 316L stainless steel. Flush black silk-screened glass extra-clear tempered, 4mm thick. Available in single and bi-emission versions in three distinct diameters for different design needs. 21°, 45° and 65° optics with colour temperatures of 2700K, 3000K and 4000K. Integrated power supply. HCT surface finish available in three variants.






### LOCH M90





Color	2700 K 543 lm	3000 K 550 lm	4000 K 613 lm	Emission	21°
					45°
					65°
Power	5 W				Codes Technical details
	IP66				


### LOCH M120



Color	2700 K 741 lm	3000 K 750 lm	4000 K 836 lm	Emission	21°
					45°
					65°
Power	7 W				Codes Technical details
	IP66				

### LOCH M180



Color	2700 K 2174 lm	3000 K 2200 lm	4000 K 2453 lm	Emission	21°
					45°
					65°
Power	18 W				Codes Technical details
	IP66				



F W Lighting - The Light House - 37 Wadham Grove - Emersons Green - Bristol - BS16 7DX

+44 (0) 7891 919 169

info@fw-lighting.com

www.fw-lighting.com

LOCH B90



120



120

90

Color

2700 K

2 x 543 lm



3000 K

2 x 550 lm

4000 K

2 x 613 lm

Emission



Power  
2 x 5 W




Codes  
Technical details

IP66

IK08

LOCH B120



154

120



154

120

Color

2700 K

2 x 741 lm



3000 K

2 x 750 lm

4000 K

2 x 836 lm

Emission



Power  
2 x 7 W



Codes  
Technical details

IP66


IK08

LOCH B180



223

120



223

180

Color

2700 K

2 x 2174 lm



3000 K

2 x 2200 lm

4000 K

2 x 2453 lm

Emission



Power  
2 x 18 W



Codes  
Technical details

IP66

IK08



F W Lighting - The Light House - 37 Wadham Grove - Emersons Green - Bristol - BS16 7DX

+44 (0) 7891 919 169

info@fw-lighting.com

www.fw-lighting.com