

STRAL

LOCH M20

LOCH M20 The spacer integrated with the lamp body makes the product compact. Made of AISI 316L stainless steel. Flush black silk-screened glass extra-clear tempered, 4mm thick. Available in single and bi-emission versions in three distinct diameters for different design needs. 21°, 45° and 65° optics with colour temperatures of 2700K, 3000K and 4000K. Integrated power supply. HCT surface finish available in three variants.



LOCH M120



154



154

Color

2700 K
741 lm

3000 K
750 lm

4000 K
836 lm

Emission

21°

45°

65°

Power
7 W



Codes
Technical details


IP66

IK08

LOCH M180



223



223

Color

2700 K
2174 lm

3000 K
2200 lm

4000 K
2453 lm

Emission

21°

45°

65°

Power
18 W



Codes
Technical details

IP66

IK08

LOCH M90



120



120

Color

2700 K
543 lm

3000 K
550 lm

4000 K
613 lm

Emission

21°

45°

65°

Power
5 W



Codes
Technical details

IP66

IK08





F W Lighting - The Light House - 37 Wadham Grove - Emersons Green - Bristol - BS16 7DX

+44 (0) 7891 919 169

info@fw-lighting.com

www.fw-lighting.com

LOCH B90



Color


2700 K
2 x 543 lm


3000 K
2 x 550 lm

4000 K
2 x 613 lm

Emission

 21° + 21°

 45° + 45°

 65° + 65°

Power
2 x 5 W





Codes
Technical details

IP66

IK08

LOCH B120




Color


2700 K
2 x 741 lm


3000 K
2 x 750 lm

4000 K
2 x 836 lm

Emission

 21° + 21°

 45° + 45°

 65° + 65°

Power
2 x 7 W





Codes
Technical details

IP66

IK08

LOCH B180




Color


2700 K
2 x 2174 lm


3000 K
2 x 2200 lm

4000 K
2 x 2453 lm

Emission

 21° + 21°

 45° + 45°

 65° + 65°

Power
2 x 18 W



Codes
Technical details

IP66

IK08



F W Lighting - The Light House - 37 Wadham Grove - Emersons Green - Bristol - BS16 7DX

+44 (0) 7891 919 169

info@fw-lighting.com

www.fw-lighting.com