



Only
13.5mm
Dia

88.364.52

| | | |
|--------------------------|-----------------------------------|---|
| Surface: | brushed antique brass 52 | Ultra Slim semi-recessed luminaire |
| Lamp socket: | 1 x LED integrated / 350 mA / 1 W | antique brass brushed |
| Height: | 30 mm | incl. 1 watt LED warm white |
| Diameter: | 13,5 mm | incl. LED driver (added as loose part) |
| Wattage: | 1 W | Ø ca. 13,5 mm, Ø cover plate ca. 25 mm height |
| Voltage: | 350 mA | ca. 30 mm |
| Protection class: | III | |
| Safety norm: | CE | |

0,9W @ 350mA - 2700K / CRI>90 / 110 lm (117lm/W) - with Ledil-lens @ 96,8 lm output
2,0W @ 700mA - 2700K / CRI>90 / 203 lm (102lm/W) - with Ledil-lens @ 178,6 lm output

Upon request:

0,9W @ 350mA - 3000K / CRI>90 / 110 lm (117lm/W) - with Ledil-lens @ 96,8 lm output
2,0W @ 700mA - 3000K / CRI>90 / 203 lm (102lm/W) - with Ledil-lens @ 178,6 lm output

0,9W @ 350mA - 4000K / CRI>90 / 120 lm (127lm/W) - with Ledil-lens @ 105,6 lm output
2,0W @ 700mA - 4000K / CRI>90 / 221 lm (112lm/W) - with Ledil-lens @ 194,5 lm output